



## DAMP Features:

- 5 -1000 MHz with 5-42 MHz passive
- "F" ports brass connectors nickel plated
- "F" ports waterproof to withstand 1kg/cm<sup>2</sup> air pressure
- LED power indicator; power adaptor included
- Heavy duty housing epoxy tongue & groove sealed
- Available in 1 port and 4 port models

	DAMP-1	DAMP-4	
Forward Frequency	54-1000	54-1000	MHz
Return Frequency	5-42	5-42	MHz
Typical Gain	15	8	dB
Response Flatness	1	1	dB
Number of Output Ports	1	4	
Return Loss	-16	-16	dB
Channel Load	77	77	
Rated Output Level	29	25	dBmV
CTB	-74	-74	dB
CSO	-70	-70	dB
Noise Figure	3	3	dB
Hum Modulation	-70	-70	dB
Power Consumption	2.5 W / 110 V	2.5 W / 110 V	
Return Insertion Loss	-0.5	-7.5	dB

- Specification subject to change without notice

	Std Qty	Std Weight	Dimension (LxWxH)
DAMP-1 (One port)	1	0.45 kg (1 lb)	12x3x11 cm (4.7x1.2x4.3 in)
DAMP-4 (Four port)	1	0.45 kg (1 lb)	12x3x11 cm (4.7x1.2x4.3 in)